



	TRIPLE BANK CONSUMER UNIT		
	<b>54</b>	<b>45</b>	<b>44</b>
NUMBER OF USABLE WAYS(MODULES)			
PART NUMBER	<b>F2048E</b>	<b>F2045M</b>	<b>F2044MX</b>
DESCRIPTION	54 MODULE MAX ENC INCLUDING BUSBAR + CABLES	100A MAIN SWITCH 45 WAY	100A MAIN SWITCH 44 WAY T2 SPD
GTIN-13	<b>18/18/18</b> 5060523524648	<b>15/15/15</b> 5060523524624	<b>14/15/15</b> 5060523524631
CARTON QUANTITY	2	2	2
DIMENSION DRAWING	48P	48P	48P
WEIGHT (1PC) Kg			
DIMENSIONS (HxWxD)mm	762x378x113	762x378x113	762x378x113
TRIPLE BANK	Y	Y	Y
TAIL CLAMP INCLUDED (ACCF)	N	N	Y
STANDARD			BS EN 61439-3
RATED VOLTAGE (Un/AC)			230V
FREQUENCY (Hz)			50/60
PROTECTION DEGREE (IP)			2XC
MAXIMUM TERMINAL BAR CAPACITY			16mm <sup>2</sup>
TERMINAL BAR TIGHTENING TORQUE (Nm)			2.0
DEVICE MOUNTING			35mm DIN RAIL
MATERIAL			1mm ELECTRO GALVANISED STEEL (ZINC)
FINISH			RAL 9001 POWDER COATED SMOOTH FINISH
KNOCKOUTS			SELECTION 20mm - 32mm
ACCESSORY PACK			CIRCUIT IDENTIFICATION LABELS / GROMMET STRIP <i>(BUSBAR x3 / Neutral cable x3 INCLUDED IN F2048E)</i>
ORIGIN OF MANUFACTURE			CHINA

DIMENSIONS

48P

